

ON-9

Power by Perkins

403D-11G

Prime power: 7KW/9KVA

Standby power: 8KW/10KVA

GENERATING POWER SOLUTIONS

Increased availability for new operations

Reliable, robust and versatile generator.
Ready to deliver power for a next job.

Increased uptime during operations

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

Reduced transport and installation costs


The compact and robust design with integrated transport features enables faster and safer transport and installation.

Reduced service & maintenance costs

Longer service intervals.
Quicker and more efficient service jobs.

Premium resale value

Designed and built to last.



DIMENSION			OPEN TYPE	SILENT TYPE
	Length (L)	mm	1620	2602
	Width (W)	mm	950	1100
	Height (H)	mm	1400	1525
	Dry weight	kg	950	1500
	Fuel tank	L	100	100

ONEWPOWER

WWW.ONEWPOWER.COM

Technical Data

Model ON-9

Rated prime power	KW	7
Rated standard power	KW	8
Rated voltage line to line	V	380~415
Maximum sound level	dB(@7m)	≤ 72

Engine

Model		403D-11G
Aspiration		Naturally aspirated
Fuel system		mechanical pump
No. cylinders		3
Displacement	Liquid	1.131
Bore*Stroke	mm	77*81
Compression ratio		23:1
Rated speed	r/min	1500
Rated net power(with fan)	Kw	8
Governor type		Mechanical

Exhaust system

Exhaust gas flow		1.66 m³/min
Exhaust gas temp	° F (° C)	<368
Max back pressure		10. 2kPa

Aspiration system

Max inlet pressure	kPa	≤3.5
Combustion volume	L/s	/
Air flow	L/sec	TBA

Fuel system

100% load(Prime power)	L/h	2.7
75% load(Prime power)	L/h	2.1
50% load(Prime power)	L/h	1.5
Fuel tank capacity	L	100

Lubrication system

Oil capacity	L	4.9
Oil consumption	g/kwh	28.3
Oil pressure	kPa	10
(continuous operation)		

Cooling system

Coolant capacity	L	5.2
Thermostat operation range	°C	76-88
Max water temperature	°C	98

Alternator

Model		ON-9
Phase		3
Voltage	V	380~415
Bearing		1
Power factor		0.8
Frequency	Hz	50
Prime power	KW	7
Exciter Type		Brushless, self-excitation
Voltage regulation	%	±1.0
Protection Grade		IP 23
Insulation grade		H/H
Altitude	m	≤1000

Controller

Model		
Protective functions:		
■ Low oil pressure		
■ High water temperature		
■ High/low voltage		
■ High Engine Temperature and Overspeed.		
■ Voltage regulator frequency regulator		
■ Emergency stop		
■ Start failure		



Control Module Options



- Auto generator control module
- Control module with "Three Remote Control" functions
- ATS auto load transfer screen
- Synchronising control modules
- Power output cabinet

Standard features

- Engine ●
- Radiator 50°C max,fans are driven by bel ●
- 24V charge alternator ●
- Alternator: single bearing alternator IP23, ●
- insulation class H/H ●
- Standard auto control system ●
- One set of air filter, fuel filter, oil filter ●
- Main line circuit breaker/MCCB ●
- Base fuel tank ●
- Two 24V batteries, rac and cable ●
- Exhaust system(Ripple flex exhaust pipe, ●
- exhaust siphon, flange, muffler ●
- User manual ●

Options

- Battery charge ○
- Engine heater ○
- Alternator heater ○
- PMG ○
- Water oil separator ○
- Daily fuel tank ○
- Remote control panel ○
- Automatic transfer switch/ATS ○
- Switch box ○
- Standard: ● Options:○

Warranty



CUMMINS ENGINE

12 months from date of purchase and 1000 hours.

Generator

12 months from date of purchase or 1000 hours
(whichever occurs first).

Dimensions



ONEWPOWER

ADD: NO . 1 0 7 XIYUAN ROAD , JINAN DISTRICT,
FUZHOU CITY,FUJIAN, CHINA
Phone:15980204507 E-mail:jina@onewpower.com
WWW.ONEWPOWER.COM

